



A-FC3454 wide dynamic professional camera

- Intelligent Clean Spot
- Challenge by Bright Light
- Powerful 128x WDR

Product information

Features

- 1/3" Super Hi-Res
- AES/AGC/BLC/FL Switchable
- Back Light Environment Available

Specification

Sense Up
AUTO (Limit x2-x256) / OFF

TV System
PAL, NTSC

Image Sensor
1/3" Sony Double-speed (Double-density) CCD

Signal to Noise Ratio
More Than 50dB(AGC Off, Weight On)

Synchronizing System
Internal / Line Lock

Wide Dynamic Range
128x Normal Camera (52dB)

Resolution; DSP
Color:540TVL, B/W: 560TVL

Back Light Compensation
WDR/BLC/OFF

Total Pixel
PAL: 795(H) x 596(V), NTSC: 811(H) x 508(V)


Power Supply
DC 12V

Item Measurements/ Temperature

Width 63mm
Height 52mm
Weight 400g
Length 121mm
Storage Temperature -20°C - +60°C
Operating Temperature -10°C - +50°C



12Vdc/24Vac



Minimum Illumination

Color: 0.1 Lux@F1.0, B/W: 0.01Lux@F1.2;
sense-up: 0.001Lux@F1.0