



A-DC6354

ip ir dome camera

- **Video/DC Iris Control**
- **AES/AGC/BLC/FL (Auto Sensing)**
- **30 Led for total darkness**
- **Support 3GPP (Mobile Handset Viewwing)**

Product information

Features

- **Low Lux for light sensitivity**
- **Sony HQ1/540TVL/0.1Lux/F1.2**
- **SD Card Slot, supports SDHC up to 32 GB**
- **Colour Mode Switches to B/W Mode AES/AGC/BLC/FL (Auto Sensing)**
- **Video/DC Iris Control**
- **30 Led for total darkness**

Specification

TV System
1/3" SONY HQ1 CCD

Effective Pixel (H x V)
PAL: 795(H) x 596(V); NTSC 811(H) x 508(V)

Synchronizing System
Internal

Min. Illumination
Color: 0.1Lux@F1.0; B/W: 0.05Lux@F1.0

Electronic Shutter
Automatic, 1/50(60) sec, -1/100,000sec

Auto Gain Control & White Balance
Auto

AES & Back Light Compensation
Auto

Signal to Noise Ratio
More than 50dB (AGC OFF)

Image compression
MPEG4 / H.264

Item Measurements/ Temperature

Dia 150mm
Height 150mm
Storage Temperature -20°C - 60°
Operating Temperature -10°C - 50°C

Image Frame Rate
25fps@ 720x576; 30fps@ 720x480

Max. Resolution
Full D1/CIF/QCIF

Ethernet
10/100 base-T for LAN/WAN

Supported Protocol
TCP,UDP,IP,HTTP,DHCPV,PPPoE,RTP,RTSP,
SMB,SMTP

QoS
Layer 2, 3

Network
RJ-45 port (WAN/LAN)

Card Slot
MicroSD Card (support up to 32GB SDHC internal
Storage)

Serial Port
1xRJ-45 port (RS485)

Power Supply
12Vdc / PoE (Optional)

Resolution
540 TVL