



A-FC6654 ip ir outdoor camera

- **Low Lux for light sensitivity**
- **AES/AGC/BLC/FL (Auto Sensing)**
- **Support 3GPP**

Product information

Features

- **Low Lux for light sensitivity**
- **Sony HQ1/540TVL/0.1Lux/F1.2**
- **SD Card Slot, supports SDHC up to 32 GB**
- **Colour Mode Switches to B/W Mode**
- **AES/AGC/BLC/FL (Auto Sensing)**

Specification

TV System

1/3" SONY HQ1 CCD

Effective Pixel (H x V)

PAL: 795(H) x 596(V); NTSC 811(H) x 508(V)

Synchronizing System

Internal

Min. Illumination

Color: 0.1Lux@F1.0; B/W: 0.05Lux@F1.0

Electronic Shutter

Automatic, 1/50(60) sec, -1/100,000sec

Auto Gain Control & White Balance

Auto

AES & Back Light Compensation

Auto

Signal to Noise Ratio

More than 50dB (AGC OFF)

Image compression

MPEG4 / H.264

Item Measurements/ Temperature

Dia 150mm

Height 132mm

Storage Temperature -20°C - 60°

Operating Temperature -10°C - 50°C

Image Frame Rate

25fps@ 720x576; 30fps@ 720x480

Max. Resolution

Full D1/CIF/QCIF

Ethernet

10/100 base-T for LAN/WAN

Supported Protocol

TCP,UDP,IP,HTTP,DHCPV,PPPoE,RTP,RTSP, SMB,SMTP

QoS

Layer 2, 3

Network

RJ-45 port (WAN/LAN)

Card Slot

MicroSD Card (support SDHC up to 32GB)

Serial Port

1xRJ-45 port (RS485)

Power Supply

12Vdc / PoE (Optional)

Resolution

540 TVL