



A-FC3000

ip pan / tilt camera

- **Mega Pixel CMOS**
- **AES/AGC/BLC/FL (Auto Switch)**
- **Support Image Inverting**

Product information

Features

- Low Lux for light sensitivity/
- Mega pixel CMOS
- SD card slot, supports SDHC up to 32 GB
- AES/AGC/BLC/FL (auto switch)
Support 3GPP (mobile viewing)
- Support image inverting

Specification

TV System
Mega Pixel CMOS

Resolution (H x V)
VGA 640 x 480

Synchronizing System
Internal

Min. Illumination
Color: 0.1Lux@F1.0

Electronic Shutter
N.A

Auto Gain Control & White Balance
Auto

AES & Back Light Compensation
Auto

Signal to Noise Ratio
More than 50dB (AGC OFF)

Image compression
MPEG4 / H.264

Item Measurements/ Temperature

Width 110mm
Height 50mm
Length 50mm
Storage Temperature -20°C - 60°C
Operating Temperature -10°C - 50°C

Image Frame Rate
25fps@ 720x576; 30fps@ 720x480

Max. Resolution
Full D1/CIF/QCIF

Ethernet
10/100 base-T for LAN/WAN

Supported Protocol
TCP,UDP,IP,HTTP,DHCP,PPPoE,RTP,RTSP,
SMB,SMTP

QoS
Layer 2, 3

Network
RJ-45 port (WAN/LAN)

Card Slot
MicroSD Card (support up to 32GB SDHC internal
Storage)

Serial Port
1xRJ-45 port (RS485)

Power Supply
12Vdc / PoE (Optional)